

Oracle SBC - Reject calls

Verify system health

```
usdensbc2# set-system-state offline
Are you sure you want to bring the system offline? [y/n]?: y
Setting system state to going-offline, process will complete when all current
SIP calls and SIP registrations have completed
usdensbc2# show health

Media Synchronized      true
SIP Synchronized        true
REC Synchronized        true
XSERV Synchronized      disabled
Config Synchronized     true
Collect Synchronized    disabled
RADIUS CDR Synchronized true
Rotated CDRs Synchronized true
IPSEC Synchronized      disabled
Iked Synchronized       disabled
Lbpd Synchronized       disabled
tCCD Synchronized       disabled
Service Health Synchronized true
Active Peer Address

Redundancy Protocol Process (v3):
State      Active
Health     100
Lowest Local Address      s.s.s.s
1 peer(s) on 2 socket(s):
usdensbc1: v3, Standby, health=100, max silence=1050
last received from 1x.x.x.x on wancom1:0
```

Set system offline

```
usdensbc2# set-system-state offline
Are you sure you want to bring the system offline? [y/n]?: y
Setting system state to going-offline, process will complete when all current
SIP calls and SIP registrations have completed
usdensbc2#
```

To specify reject response

```
usdensbc2# config t
usdensbc2(configure)# session-router
usdensbc2(session-router)# sip-config
usdensbc2(sip-config)# select
usdensbc2(sip-config)# show
sip-config
state                enabled
operation-mode       dialog
dialog-transparency  enabled
home-realm-id
egress-realm-id
auto-realm-id
nat-mode              None
registrar-domain
registrar-host
registrar-port        0
register-service-route always
init-timer            500
max-timer             4000
trans-expire          32
initial-inv-trans-expire 0
invite-expire         180
session-max-life-limit 0
inactive-dynamic-conn 32
enforcement-profile
pac-method
pac-interval          10
pac-strategy          PropDist
pac-load-weight       1
pac-session-weight    1
pac-route-weight      1
```

pac-callid-lifetime	600
pac-user-lifetime	3600
red-sip-port	1988
red-max-trans	10000
red-sync-start-time	5000
red-sync-comp-time	1000
options	max-udp-length=0 reinvite-trying=yes sag-target-uri=ip
spl-options	
add-reason-header	disabled
sip-message-len	4096
enum-sag-match	enabled
extra-method-stats	enabled
extra-enum-stats	disabled
mpps-volte	disabled
rph-feature	disabled
nsep-user-sessions-rate	0
nsep-sa-sessions-rate	0
registration-cache-limit	0
register-use-to-for-ip	disabled
refer-src-routing	disabled
add-ucid-header	disabled
proxy-sub-events	
allow-pani-for-trusted-only	disabled
atcf-stn-sr	
atcf-psi-dn	
atcf-route-to-sccas	disabled
eatf-stn-sr	
pass-gruu-contact	disabled
sag-lookup-on-redirect	disabled
set-disconnect-time-on-bye	disabled
refer-reinvite-no-sdp	disabled
msrp-delayed-bye-timer	15
transcoding-realm	
transcoding-agents	
create-dynamic-sa	disabled
node-functionality	P-CSCF
match-sip-instance	disabled
sa-routes-stats	disabled
sa-routes-traps	disabled

rx-sip-reason-mapping	disabled
add-ue-location-in-pani	disabled
hold-emergency-calls-for-loc-info	0
retry-after-upon-offline	0
reg-reject-response-upon-offline	503
hold-invite-calls-for-loc-info	0
cache-loc-info-expire	32
msg-hold-for-loc-info	0
npli-upon-register	disabled
start-hold-timer-event	AAR
hist-to-div-for-cause-380	inherit
anonymize-history-for-untrusted	disabled
sms-report-timeout	32
user-agent	
last-modified-by	admin@x.x.x.x
last-modified-date	2020-07-14 16:00:24

Revision #2

Created 28 April 2023 20:58:12 by Cesar Gzz

Updated 28 April 2023 21:05:17 by Cesar Gzz